

JLG 150HAX



- Largest self-propelled lift in the world at a working height of 47 m
- Longest outreach at 24.16 m of any self-propelled lift in the world
- Up and over height 24.38 m
- Fast boom and drive speeds improve work productivity
- Four wheel drive and four wheel steer is standard
- Proportional controls achieve smoother movement for operator comfort
- Excellent manoeuvrability for positioning of machine and platform

For more details check the JLG Technical Specification Guide or ask your local JLG representative.



Proportional Drive Controls

Proportional controls provide operation for telescoping the main and tower boom and drive, lift and swing.



Moveable Ground Control

The ground controls can be detached from the machine housing to aid the operator when loading the machine for transport.



Plate Steel Boom

Provides longer service life and minimal deflection for operator comfort.



165° Powered Rotator

A sealed hydraulic platform rotator with 165 degrees of motion for improved positioning.



Ground to Platform Intercom System

An intercom system is supplied to permit communication between platform and ground personnel.



Extending Axles

Help to reduce stowed width for travel in confined areas and for ease of transport.

150 HAX ARTICULATING BOOM LIFT

150HAX

Platform Height	45.72 m
Horizontal Outreach	24.16 m
Up and Over Height	24.38 m
Swing (Continuous)	360°
Platform Capacity – Unrestricted	230 kg
Platform Rotator (Hydraulic)	165°
A. Platform Size	0.91 m x 2.44 m
B. Overall Width (Axles Retracted)	3.51 m
C. Overall Width (Axles Extended)	5.49 m
D. Tailswing (working condition)	Zero
E. Stowed Height	4.27 m
F. Stowed Length	12.01 m
G. Wheelbase	5.49 m
H. Ground Clearance	0.30 m
Gross Vehicle Weight*	25,855 kg
Maximum Ground Bearing Pressure	7.9 kg/cm ²
Maximum Tyre Load	12,000 kg
Drive Speed	4.3 km/h
Gradeability	31%
Tyres	445/65R22.5 Foam Filled
Turning Radius (Inside) - Axles Retracted	4.52 m
Turning Radius (Inside) - Axles Extended	4.45 m
Turning Radius (Outside) - Axles Retracted	8.23 m
Turning Radius (Outside) - Axles Extended	9.17 m
Diesel Engine – Cummins 4B3-9C	58 kW
Fuel Tank Capacity	257.4 L
Hydraulic Reservoir	469.3 L
Auxiliary Power	12V DC

*Certain options or country standards will increase weight.

Specifications may change to meet country standards or with the addition of optional equipment.

