



**facelift**  
access and safety made easy

Construction Grade  
**ELECTRIC**  
Rough Terrain  
Speed Level™  
Sigma Lifts

Model  
2684ES SPEED LEVEL™  
3084ES SPEED LEVEL™

- All ELECTRIC rough terrain
- Up to 36 ft. (11m) working height
- Fast platform leveling on slopes, automatic or manual selection, with an amazing 14° side to side and 10° fore and aft oscillation
- Up to 1,700 lbs (770 kg) platform capacity
- Quad-Trax 4wd power package giving 40% gradeability
- Proportional drive and lift controls
- Non-skid metal deck construction
- Large sheet loading entrances (fore and aft)
- No-maintenance bearings
- Incredible ground clearance



## Features

### Work Area

Automatic and Manual Platform Leveling  
 Large sheet loading entrance accommodates 48"  
 (1.22 m) material  
 110V Power to Platform

### Performance

Proportional Drive and Lift Controls  
 High Torque Power Package

### Power

Eight 6V 370 Ah Industrial Deep-Cycle Batteries

### Serviceability

Lubrication-free Bearings  
 Easy maintenance access to mechanical and electrical  
 components  
 Logically grouped components and numbered wiring  
 for easy reference

### Safety

Dedicated compartments protect electrical and  
 hydraulic components  
 Emergency shut-off at platform and lower controls  
 Non-Skid Metal Deck Construction  
 Motion Alarm  
 Drive Speed Interlock  
 Multi-Axis Tilt Sensor  
 Multiple Disc Brakes, Manual Brake Release  
 Dual Automatic Parking Brake

### Other Features

Platform Swing Gate  
 Fold-down Guardrail  
 Hour Meter  
 Powder Coat Finish  
 Machine Tie Downs  
 Battery Charge Indicator

## Optional Features

Lanyard Attachments (6)  
 Flashing Beacon (continuous)  
 Quad-Trax 4wd Power Package  
 Automotive Horn  
 Removable Upper Controls  
 Air Line to Platform  
 Audible Motion Alarm  
 415 Ah Deep Cycle Batteries  
 AC Inverter  
 Foam-Filled Tires  
 Non-Marking Tires  
 Turf Tires  
 CE Compliant Options  
 Australian Compliant Options  
 CSA Compliant Options  
 1 or 2 Year Extended Warranty



Model	2684ES Speed Level™		3084ES Speed Level™	
	U.S.	Metric	U.S.	Metric
<b>Heights</b>				
Working Height*	32 ft.*	9.75 m*	36 ft.*	11 m*
Platform Height	26 ft.	7.93 m	30 ft.	9 m
Maximum Drive Height	26 ft.	7.93 m	30 ft.	9 m
Stowed Height (Top Guardrail)	105 in.	2.67 m	105 in.	2.67 m
Stowed Height (Rails Folded)	70 in.	1.78 m	70 in.	1.78 m
Guardrail Height	43½ in.	1.1 m	43½ in.	1.1 m
Toeboard Height	6 in.	15 cm	6 in.	15 cm
Ground Clearance	10 in.	25 cm	10 in.	25 cm
<b>Dimensions</b>				
Length - Stowed (Overall)	12 ft. 6 in.	3.8 m	14 ft. 6 in.	4.4 m
Width	84 in.	2.13 m	84 in.	2.13 m
Platform Length	12 ft.	3.65 m	14 ft.	4.27 m
Platform Length (Extended)	15 ft.	4.57 m	-	-
Platform Width	72 in.	1.83 m	72 in.	1.83 m
Wheelbase	100 in.	2.54 m	100 in.	2.54 m
Lift Capacity	1,700 lbs.	770 kg	1,500 lbs.	680 kg
Extension Deck Lift Capacity	500 lbs.	227 kg	-	-
Structure Leveling	14° side to side, 10° fore and aft		14° side to side, 10° fore and aft	
<b>Speeds</b>				
Raise/Lower Speed	30/35 sec.		35/40 sec.	
Drive Speed (Stowed)	3 mph	4.8 km/h	3 mph	4.8 km/h
Drive Speed (Raised)	.4 mph	.6 km/h	.4 mph	.6 km/h
<b>Performance</b>				
Gradeability	40%/22°		40%/22°	
Turning Radius (Inside)	8 ft.	2.44 m	8 ft.	2.44 m
Turning Radius (Outside)	16 ft. 8 in.	5.08 m	16 ft. 8 in.	5.08 m
Weight **	8,100 lbs**	3675 kg**	8100 lbs**	3675 kg**
Brakes	Dual rear wheel multi-disc			
Power Source	Eight 6V 370 Ah industrial deep-cycle batteries			
Controls	Proportional			
Tires	26 X 12D / 380NHS			
Hydraulic Fluid Capacity	23 gal.	87 L	23 gal.	87 L

\*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

\*\*Weight may vary with certain options or configurations. When platform is elevated, all models must be on a firm, planar surface.



Warranty – MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.6-2006, CSA B354.2-01, AS 1418.10 and CE Compliance as applicable. Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.



**Head Office**  
 Westside, London Road,  
 Hickstead, West Sussex,  
 RH17 5LZ  
 T 01444 88 11 88  
 F 01444 88 11 99  
 E hiredesk@facelift.co.uk  
 W facelift.co.uk