



facelift
access and safety made easy

Industrial Grade Electric Scissor Lifts

Models
3072 ES
3772 ES
3772 ES HD

- Fully proportional drive and lift controls
- No-maintenance scissor bearings
- Roll-out deck extension with incremental locking positions
- Non-skid, steel deck construction
- Large sheet loading entrance
- Single arm scissor provides easy access for maintenance. No need for swing-out stations or tight working conditions.
- Patented Powerlift² elevating system - built strong and works tough
- Quad-Trax™ 4wd power package
- Outrigger support for platform stability on heavy duty jobs sites with "one-touch" auto leveling
- 60 sq. ft. platform space



Features

Work Area

Roll-out deck extension with incremental locking positions
Large sheet loading entrance accommodates 48" (1.22 m) material

110V Power to Platform

Combination of wide beams and large pins in self-lubricating bearings for larger load bearing surface in scissor pivot areas

Performance

Fully proportional drive and lift controls

Quad-Trax™ 4wd Power Package

Engine/Power

Eight 6V 350Ah Industrial, Deep Cycle Batteries

Serviceability

Lubrication-Free Scissor Bearings

Easy maintenance access to mechanical and electrical components without raising platform or swinging out trays

Logically grouped components and numbered wiring for easy reference

Safety

Dedicated compartments protect electrical and hydraulic components

Emergency shut-off at platform and lower controls

Non-Skid Steel Deck Construction

Motion Alarm

Drive Speed Interlock

Multi-Axis Tilt Sensor

Multiple Disc Brakes, manual brake release

Scissor Maintenance Lock

Dual Automatic Parking Brake

Other Features

Industrial grade, solid-state battery charger

Fold Down Guardrails

Hour Meter

Powder Coat Finish

Lifting Lugs

Machine Tie Downs

U.S. Patent #5,476,050

Canadian Patent #2,115,870

Other Patents Pending

Optional Features

Lanyard Attachments (6)

Flashing Beacon (continuous)

Automotive Horn

Removable Upper Controls

Platform Swing Gate (standard on CE and CSA)

Air Line to Platform

All Motion Alarm

Battery Charge Indicator

Quad-Trax™ 4wd

Auto-Leveling Outriggers (standard on 3772ES HD)

Platform Work Lights

120V 2250W Generator

Non-Marking RT Tires

Foam Filled Tires

Turf Terrain Tires

Australian Compliant Options

CSA Compliant Options

1 or 2 Year Extended Warranty



Model	3072ES		3772ES		3772ES HD	
	U.S.	Metric	U.S.	Metric	U.S.	Metric
Heights						
Working Height*	36 ft.*	11.14 m*	43 ft.*	13.28 m*	43 ft.*	13.28 m*
Platform Height	30 ft.	9.14 m	37 ft.	11.28 m	37 ft.	11.28 m
Maximum Drive Height	30 ft.	9.14 m	37 ft.	11.28 m	37 ft.	11.28 m
Stowed Height (Top Guardrail)	108½ in.	2.75 m	106¾ in.	2.71 m	106¾ in.	2.71 m
Stowed Height (Rails Folded)	78 ½ in.	2.00 m	77 in.	1.95 m	77 in.	1.95 m
Guardrail Height	43½ in.	1.10 m	43½ in.	1.10 m	43½ in.	1.10 m
Toeboard Height	6.0 in.	15 cm	6.0 in.	15 cm	6.0 in.	15 cm
Ground Clearance	9½ in.	24.1 cm	9½ in.	24.1 cm	9½ in.	24.1 cm
Dimensions						
Length - Stowed (Overall)	117¼ in.	2.98 m	117¼ in.	2.98 m	117¼ in.	2.98 m
Width	72 in.	1.83 m	72 in.	1.83 m	72 in.	1.83 m
Platform Length (Extended)	158 in.	4.01 m	158 in.	4.01 m	158 in.	4.01 m
Platform Length (Retracted)	110 in.	2.79 m	110 in.	2.79 m	110 in.	2.79 m
Roll-Out Deck Length	48 in.	1.22 m	48 in.	1.22 m	48 in.	1.22 m
Wheelbase	86 in.	2.18 m	86 in.	2.18 m	86 in.	2.18 m
Lift Capacity (Without Outriggers)	1,000 lbs	454 kg	750 lbs	340 kg	—	—
Lift Capacity (With Outriggers)	1,000 lbs	454 kg	1,000 lbs	454 kg	1,000 lbs	454 kg
Roll-Out Deck Capacity	400 lbs	181 kg	400 lbs	181 kg	400 lbs	181 kg
Speeds						
Raise/Lower Speed	36/24 sec.		40/30 sec.		40/30 sec.	
Drive Speed (Stowed)	3.0 mph	4.8 km/h	3.0 mph	4.8 km/h	3.0 mph	4.8 km/h
Drive Speed (Raised)	0.4 mph	0.6 km/h	0.4 mph	0.6 km/h	0.4 mph	0.6 km/h
Performance						
Gradeability	45%/26°		40%/22°		40%/22°	
Turning Radius (Inside)	73 ¼ in.	1.86 m	73 ¼ in.	1.86 m	73 ¼ in.	1.86 m
Turning Radius (Outside)	14 ft. 2½ in.	4.33 m	14 ft. 2½ in.	4.33 m	14 ft. 2½ in.	4.33 m
Weight (Approximately**)	7,868 lbs**	3568 kg**	8,195 lbs**	3717 kg**	8,815 lbs**	3998 kg**
Brakes	Multiple disc brakes, dual rear wheel					
Power Source	Eight 6V 350Ah industrial, deep cycle batteries					
Controls	Proportional drive and lift controls					
Tires	26 x 12D / 380 NHS					

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

**Weight may increase with certain options or country standards. When platform is elevated, all models must be on a firm, level surface.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only.

Meets or exceeds the requirements of ANSI A92.6-2006, CSA B354.2-01, AS 1418.10 and CE Compliance as applicable. Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Head Office
Westside, London Road,
Hickstead, West Sussex,
RH17 5LZ

T 01444 88 11 88
F 01444 88 11 99
E hiredesk@facelift.co.uk
W facelift.co.uk

facelift
access and safety made easy