

towermatic®

SAVE TIME & MONEY

– Safely

Towermatic signifies a revolutionary step forward in the provision of safe, flexible and economical work platforms.

Part scissor lift part alloy access tower towermatic represents a unique crossover product combining many of the benefits of alloy tower with those of small to medium size scissor lifts at an affordable price.

Ease of use, minimal training and no PASMA or IPAF certification requirement make towermatic a highly desirable and competitive alternative to traditional scissor lifts.

Operation is simple. Once the unit has been safely deployed and the platform cage assembled, depressing the mechanism release bar unlocks the height adjusters and activates the patented, failsafe tension system. This allows the operator to manually raise or lower the work platform to a maximum height of four metres in seconds, smoothly and silently. Stepping off the foot control bar double locks the tower at the desired height. Access to the work platform is gained by the integral ladder.

Towermatic provides a large, safe and stable platform for up to two operatives.

Towermatic can be easily manoeuvred and erected by one person and requires minimal training and hand-over procedures.

- Work platform height variable to 4 metres
- Raised and lowered in seconds
- Rapidly and easily deployed
- Two man capacity (250kg SWL)
- Minimal maintenance requirement
- No Loose Parts



CE

facelift
access and safety made easy

- No Engine/batteries
- No External Power Requirement
- Lightweight Alloy construction
- Integral Access Ladder
- Climbing fall restraint hoops
- Integral additional stability outriggers
- Levelling capability
- Industry Standard Locking Castors
- Electrically Insulated
- Fall arrest lashing ring
- Locking fold away handrails
- Forklift Access rails
- Patent Pending
- Conforms to all relevant industry Standards



Variable Height



Deck Hatch Access



Additional Stabilisers



Integral Ladder



Large Work Platform

SPECIFICATION		
Maximum Platform Height		4 metres
Maximum working Height		6 metres
Closed Height		1910mm
Dimensions	L x W	1670 x 995mm
Total Weight		320 Kg
Time to full height		10 Seconds
Work Platform Capacity	SWL	250 Kg
Work Platform Size	L x W	1320 x 750mm
Aluminium Grade		6082 T6
SAFETY		
CE		Complies
EC Machinery Directive 98/37/EC		Complies
Designed and manufactured with reference to, or application of Standards		BS EN 280: 2001, BS 1139-3: 2001, BS EN ISO 12100-1: 2003, BS EN 294: 1992, BS EN 349: 1993, BS EN 547-1: 1997, BS EN 547-2: 1997, BS EN 547-3: 1997, BS EN 811: 1997, BS EN 953: 1998, BS EN 1050: 1997

NB. All dimensions are nominal.
Towermatic is a patented and registered design.



Easy to Transport



Bespoke Trailer

For further information on machine sales contact:

Mr. Mark Pugh

Facelift GB Ltd. Web: www.facelift.co.uk

Westside, London Road, Hickstead,

West Sussex, RH17 5LZ, England.

Tel: +44 (0) 1444 880913 Fax: +44 (0) 1444 881199

Email: mpugh@facelift.co.uk