

A Perfect 10

1 MORE HEIGHT HERE

Platform elevates workers and cargo a full 3.05 m (10 ft.), providing 4.88 m (16 ft.) of reach for restocking and an endless number of tasks.

2 MORE ROOM HERE

Extra large material tray is mounted on a steel frame for durability and provides 28% more cargo space than others.

3 MORE CAPACITY HERE

Transports up to 272 kg (600 lbs.) – 160 kg (350 lbs.) in the operator compartment and 112 kg (250 lbs.) on the material tray.

4 MORE CONTROL HERE

Advanced Point & Go® drive and steer joystick control leaves one hand free.

6 MORE STANDARD FEATURES HERE

Meets requirements of international standards including platform rail configuration, alarms and operations of controls.

5 MORE UPTIME HERE

Maintenance-free components minimise service needs and maximise uptime.

8 MORE RUNTIME HERE

Standard maintenance-free battery provides 25% more duty cycles than others.

7 MORE MOBILITY HERE

Zero turning radius for excellent manoeuvrability in confined spaces.

10 MORE DURABILITY EVERYWHERE

Built tough and backed by our 1 & 5 warranty for worry-free performance.


9 LESS CHARGE TIME HERE

High-efficiency charging system with 50% faster charge time than others in its class.

Find out how you can achieve higher profits, faster payback and improved worker safety with the JLG SSV10.

Visit www.jlg.com or

call +44 (0) 1698 811005.



The Power To Do More

SSV10

STORE SUPPORT VEHICLE

TYPICAL APPLICATIONS

From the back warehouse to the front of the store, the JLG SSV10 offers a higher, stronger and smarter productivity choice for hundreds of daily employee tasks.

- Stock Picking and Restocking Shelves
- Transporting Supplies
- Inventory Management
- Display Set-Up
- Hanging Decorations
- General Maintenance and Repair



STANDARD FEATURES

- Point & Go® Drive and Steer System
- One Hand Joystick Control
- Proportional Drive and Elevate Controls
- Sealed Maintenance-Free Batteries
- Automatic 5 Hour, 20 Amp Charger
- Battery Discharge Status Indicators at Platform and Base Controls
- Heavy-Duty Aluminum Mast Sections
- Maintenance-Free Mast Guide System
- Strobe Lights Front & Rear
- Programmable Alarm
- Descent Alarm and Amber Warning
- Slope Cut-Out Control Interlock
- Mast Storage Pocket
- Stand-On Foot Switch Operation Enable Control
- Platform Gate Operation Interlock
- Separate Drive and Elevation Controls
- Extra Large Material Tray 0.66 m x 0.66 m (26 in. x 26 in.)
- Adjustable Tray Height
- Built-In Fork Truck Pockets
- Non-Marking Tyres
- Hourmeter
- Horn
- CE, ANSI, OSHA, & CSA Compliant
- JLG "1 & 5" Warranty

OPTIONS

- Charger Cord Retractor
- Programmable 4-Digit Security Lock
- Bike Carrier Accessory
- Rug Carrier Accessory
- Fluorescent Light Tube Caddy
- Guide Roller System
- Side and Front Bumpers

SPECIFICATIONS

Working Height	4.88 m (16 ft.)	Maximum Tray Stowed Height	1.32 m (4 ft. 4 in.)
Platform Height	3.05 m (10 ft.)	Maximum Tray Elevated Height	4.04 m (13 ft. 3 in.)
Overall Width	75 cm (29.5 in.)	Maximum Drive Speed	
Overall Length	1.52 m (60 in.)	Platform Lowered	6.4 km/h (4 mph)
Overall Stowed Height	1.42 m (56 in.)	Platform Elevated	0.96 km/h (0.6 mph)
Gross Vehicle Weight	454 kg (1,000 lbs.)	Turning Radius	Zero
Operator Compartment Capacity	160 kg (350 lbs.)	Gradeability	15%
Material Tray Capacity	112 kg (250 lbs.)	Wheel Diameter & Width	
Combined Capacity	272 kg (600 lbs.)	Drive Wheel	32 x 10 cm (12 ⁵ / ₈ x 4 in.)
Platform Size (L x W)	51 x 69 cm (20 x 27 in.)	Front Caster	20 x 6 cm (8 x 2 ¹ / ₂ in.)
Platform Entry Height	33 cm (13 in.)	Wheel Material	Non-Marking Poly
Platform Entry	Rear – Saloon Door Gates	Battery	Maintenance-Free AGM (x 2)
Material Tray Dimensions (L x W)	66 x 66 cm (26 x 26 in.)	Battery Charger	20 Amp Automatic
Material Tray Area	0.46 sq m (4.9 sq ft.)	Charge Time	5 Hours Maximum
Minimum Tray Stowed Height	86 cm (34 in.)	Drive System	Direct Electric

