

# nifty



## TrackDrive

### TRACK MOUNTED WORK PLATFORM

**24ft, 40ft & 50ft**  
Working heights

### Superb Gradeability

Will climb very steep  
inclines as high as 60% (31°)

### Excellent Traction

Better grip on uneven terrain

### Fully Proportional Hydraulic Controls

Ergonomic & reliable

### Weight Saving Design

Lower cost transportation and  
better fuel economy on site

### Non-Marking Tracks

Optional rubber-free tracks  
available for indoor usage

### Variable Width Tracks

Access to narrow openings  
improving versatility



# nifty



# nifty TrackDrive

Nifty's new TrackDrive platforms offer a range of capabilities to suit operator requirements. The TD24 is a compact and manoeuvrable machine capable of passing through a 2ft 6in opening making it the ideal tool for jobs where space is limited. The TD34T is available in two versions, the standard and narrow width machines. The standard version offering a wider track width for steeper or rougher terrain and the narrow version will pass through a 2ft 6in opening for restricted access. The TD50 provides an impressive working envelope and its TrackDrive base allows it to travel over ground where even a 4WD SP platform would have difficulty finding traction.



TD50



TD34T



Weight saving designs mean that site-to-site transportation is more economical. The platforms are also more efficient, allowing them to work for longer while using less fuel.



TD24

Also available are rubber-free urethane tracks. Ideal for internal or clean applications, maximising the TrackDrive's utilisation

SPECIFICATIONS	TD24	TD34TN	TD34T	TD50
<b>Height - Working</b>	30ft 10in	40ft	40ft	56ft 1in
<b>Height - Platform</b>	25ft 3in	33ft 6in	33ft 6in	49ft 6in
<b>Outreach - Working</b>	11ft 6in	20ft 1in	20ft 1in	28ft 6in
<b>Slew</b>	355°	406°	406°	355°
<b>Width - Travelling</b>	2ft 6in	2ft 6in - 3ft 8in	3ft 6in - 4ft 11in	6ft 8in
<b>Width - Working</b>	6ft 11in	9ft 7in	11ft 8in	14ft 4in
<b>Height - Stowed</b>	6ft 3in	6ft 3in	6ft 3in	6ft 10in
<b>Length</b>	12ft	12ft 11in	12ft 11in	18ft 4in
<b>Weight</b>	1,870lbs	3,894lbs	3,630lbs - 4,070lbs	6,380lbs
<b>Platform Capacity</b>	265lbs	265lbs	500lbs	500lbs
<b>Platform Size</b>	2ft x 2ft	2ft 5in x 2ft	3ft 8in x 2ft 1in	3ft 8in x 2ft 1in
<b>Drive Speed</b>	1.3 - 2.1mph	0.6 - 1.0mph	0.6 - 1.0mph	0.6 - 1.0mph
<b>Gradeability</b>	30%	60%	60%	32%
<b>Control System</b>	Fully proportional hydraulic			

Due to a policy of continuing development and improvement, Niftylift reserves the right to change any specification without notice. Please confirm exact specification before ordering.