

# nifty

## TrackDrive

### TRACK MOUNTED ACCESS PLATFORM

**9m, 12m & 17m**

Working heights

#### **Superb Gradeability**

Will climb very steep  
inclines as high as 60% (31°)

#### **Excellent Traction**

Better grip on uneven terrain

#### **Fully Proportional Hydraulic Controls**

Ergonomic & reliable

#### **Weight Saving Design**

Lower cost transportation and  
better fuel economy on site

#### **Non-Marking Tracks**

Optional rubber-free tracks  
available for indoor usage

#### **Variable Width Tracks**

Access to narrow openings  
improving versatility



# nifty



**niftylift**

# TrackDrive

With working heights of 9.70m, 12.20m and 17.10m, Nifty's new TrackDrive platforms offer a range of capabilities to suit operator requirements. The TD90 is a compact and manoeuvrable machine capable of passing through a 0.75m opening making it the ideal tool for jobs where space is limited. The TD120T is available in two versions, the standard and narrow width machines. The standard version offering a wider track width for steeper or rougher terrain and the narrow version will pass through a 0.75m opening for restricted access. The TD170 provides an impressive working envelope and its TrackDrive base allows it to travel over ground where even a 4WD SP platform would have difficulty finding traction.



**TD170**



**TD120T**



**TD90**

Weight saving designs mean that site-to-site transportation is more economical. The platforms are also more efficient, allowing them to work for longer while using less fuel.

Also available are rubber-free urethane tracks. Ideal for internal or clean applications, these tracks will increase the number of locations that the TrackDrives can work, greatly improving their utilisation



Specifications	TD90	TD120TN	TD120T	TD170
<b>Height - Working</b>	9.70m	12.20m	12.20m	17.10m
<b>Height - Platform</b>	7.70m	10.20m	10.20m	15.10m
<b>Outreach - Working</b>	3.50m	6.10m	6.10m	8.70m
<b>Slew</b>	355°	406°	406°	355°
<b>Width - Travelling</b>	0.75m	0.75m - 1.15m	1.10m - 1.50m	1.85m
<b>Width - Working</b>	2.10m	2.93m	3.55m	4.37m
<b>Height - Stowed</b>	1.90m	1.90m	1.90m	2.10m
<b>Length</b>	3.70m	3.95m	3.95m	5.60m
<b>Weight</b>	850kg	1770kg	1650kg - 1850kg	2900kg
<b>Platform Capacity</b>	120kg	120kg	200kg	200kg
<b>Platform Size</b>	0.60m x 0.60m	0.75m x 0.65m	1.10m x 0.65m	1.10m x 0.65m
<b>Drive Speed</b>	1.3 - 2.1mph	0.6 - 1.0mph	0.6 - 1.0mph	0.6 - 1.0mph
<b>Gradeability</b>	30%	60%	60%	32%
<b>Control System</b>	Fully proportional hydraulic			

Due to a policy of continuing development and improvement, Niftylift reserves the right to change any specification without notice. Please confirm exact specification before ordering.