

# Model 15SP



## PUSH-AROUND STOCK PICKER



### Specifications

#### Dimensions:

|                        |                      |
|------------------------|----------------------|
| Platform Height        | 15 ft 2 in. (4.62 m) |
| Working Height         | 21 ft (6.4 m)        |
| Stowed Height          | 78 in. (198 cm)      |
| Platform Entry Height  | 17.5 in. (45 cm)     |
| Distance to Wall-Front | 0 in. (0 cm)         |
| Distance to Wall-Side  | 3 in. (7.6 cm)       |

#### Platform Capacity:

|                        |                 |
|------------------------|-----------------|
| Stock Picking Platform | 500 lb (227 kg) |
|------------------------|-----------------|

#### Platform Size (W x L):

|                        |                           |
|------------------------|---------------------------|
| Stock Picking Platform | 28 x 48 in. (71 x 122 cm) |
|------------------------|---------------------------|

#### Overall Vehicle Length:

|        |                   |
|--------|-------------------|
| Stowed | 75.5 in. (192 cm) |
|--------|-------------------|

#### Overall Vehicle Width:

|        |                |
|--------|----------------|
| Stowed | 34 in. (86 cm) |
|--------|----------------|

#### Gross Vehicle Weight:

|          |                   |
|----------|-------------------|
| DC Model | 1,240 lb (562 kg) |
|----------|-------------------|

#### Wheel Diameter:

|                                  |                |
|----------------------------------|----------------|
| Rear Wheels with Roller Bearings | 10 in. (25 cm) |
| Non-Marking Front Casters        | 6 in. (15 cm)  |

#### Battery:

Sealed 100 amp-hr Glass Mat (AGM)  
Battery Charger 5-Hour Automatic

### Features

- Low Maintenance Anodized Mast
- 28 x 48 in. (71 x 122 cm) Stock Picking Platform
- Fixed or Flexible Rail Set Up for Platform Access
- Hinged Gate for Unobstructed Front Entry
- Front and Side Entry Gates
- Removable Power Pack
- Dual Floor Brakes: One Per Side
- Safety Interlocked Controls
- 110V Double Receptacle in Platform
- Automatic 5-Hour Battery Charger
- Sealed 100 amp-hr Maintenance-Free Glass Mat (AGM) Battery
- Battery Discharge Indicator (BDI)
- Hourmeter
- Auto Power Saver—Shuts Off Power when Idle
- Key Lock Main Power Switch
- Manual Lowering Control at the Base
- Two Emergency Stop Controls—Platform and Base
- Transportation Tie Downs
- Built-In Fork Lift Pockets
- Lanyard Attachment Anchor
- Descent Alarm
- Flashing Amber Beacon
- ANSI, OSHA & CSA Compliant



### Accessories & Options

Lifting Eye for a Crane Hook

Battery Backed Emergency Lowering Control (Mounted in Platform)

Extra Power Pack

Programmable 4-Digit Security Lock

Cycle Counter

**Head Office**  
Westside, London Road,  
Hickstead, West Sussex,  
RH17 5LZ

T 01444 88 11 88  
F 01444 88 11 99  
E hiredesk@facelift.co.uk  
W facelift.co.uk

**facelift**  
access and safety made easy