

New













Safe and simple low level access

INDOOR POP-UP GOES ANYWHERE, EVEN THROUGH SINGLE DOORS.

POP-UP replaces the need for ladders and steps to be used indoors in low level access environments. Its detailed design means that it can offer a multitude of special features that ensure the user has a safe yet simple solution to low level access.

Key features and benefits

-  **Immediate low level access** - 8 seconds to reach full platform height
-  **Safe** - designed to be fully stable with a safe working load of 240 kgs
-  **Platform height** - fully extended platform height of 1.63 mtrs gives an average working height of 3.63 mtrs
-  **Easy to transport** - compact size and weight means it fits onto a small flat back vehicle and can be delivered by a single person
-  **Easy to manoeuvre** - 'smooth roll' castors system fitted means it can be positioned by a single operative
-  **Easy to operate** - simple hand set controls all elevation/de-elevation functions
-  **Training** - no formal training required to operate the POP-UP
-  **Affordable** - very competitively priced (offers good price comparison to other low level access equipment solutions)
-  **Battery powered with universal charger** - low usage and ownership costs
-  **Over 300 operations on one battery charge** - can accommodate heavy 'daily' usage requirements.



Winner of Product of the Year
Hire Awards Excellence 2006



>> SLIPS INTO LIFTS...



...AND IN AND OUT...



...OF INTERNAL DOORS



>> EASY OPERATION, NO FORMAL TRAINING NEEDED



...LIGHTWEIGHT, COMPACT AND EASY TO TRANSPORT



Pop On - Pop Up - Pop Off



High in quality, safety and versatility

Product Specification

POP-UP has been designed, manufactured and tested in accordance with both the European Standard EN280 and the safety requirements of the European Machinery Directive 98/37/EC.

Load

Safe working load (SWL)	240 kg
Equivalent to	1 person + 160 kg tools and materials

Dimensions

Maximum platform height	1.63 metres
Maximum working height	3.63 metres
Platform length	1.01 metres
Platform width	0.52 metres
Platform guard rail height	1.10 metres
Toe board height	0.15 metres
Toe board height (gate end)	0.10 metres
Maximum allowable manual force	200 Newtons
Maximum allowable wind speed	0 metres/sec
Maximum allowable chassis inclination	0 degrees

Electrical system

Voltage	12 volt DC
Motor	0.7 kW
Battery	80Ah
Battery charger	Automatic multi-voltage

Hydraulic system

Maximum pressure	250 bar
Reservoir capacity	1 litre

Function speeds (approx.)

Raise	8 seconds
Lower	8 seconds
Approx number of lifts	300 (fully charged with SWL)

Stowed dimensions

Overall length	1.135 metres
Overall height	1.636 metres
Overall width	0.700 metres

Weight

Overall mass (GVW)	215 kg
Maximum wheel load	350 kg



>> 8 SECONDS TO REACH FULL PLATFORM HEIGHT

